

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number  
**WO 2005/008077 A1**

(51) International Patent Classification<sup>7</sup>: **F15B 20/00,**  
11/024

(21) International Application Number:  
PCT/IB2004/002304

(22) International Filing Date: 16 July 2004 (16.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-276598 18 July 2003 (18.07.2003) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP]**; 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **IWASE, Yuji [JP/JP]**; Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP). **SUGAYA, Masami [JP/JP]**; Toyota Jidosha Kabushiki Kaisha,


1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP). **NISHIZAWA, Hiroyuki [JP/JP]**; Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nakagute-cho, Aichi-gun, Aichi-ken 480-1192 (JP). **HAYAKAWA, Kisaburo [JP/JP]**; Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nakagute-cho, Aichi-gun, Aichi-ken 480-1192 (JP). **OSAWA, Masataka [JP/JP]**; Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nakagute-cho, Aichi-gun, Aichi-ken 480-1192 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: HYDRAULIC CONTROL APPARATUS AND HYDRAULIC CONTROL METHOD



(57) Abstract: A hydraulic control apparatus includes two oil flow control valves (30, 32) each provided with a supply control portion (36, 38, 52, 54) for controlling an oil supply from a pressurized oil source, and a discharge control portion (40, 42, 56, 58) for controlling connection with a discharge passage. One of those oil flow control valves supplies/discharges oil to/from one of hydraulic chambers (22, 24) that are oppositely formed in a hydraulic servo mechanism. An operation direction of the hydraulic servo mechanism is performed by operating one of the oil flow control valves. The other operation direction of the hydraulic servo mechanism is performed by operating the other oil flow control valve.

WO 2005/008077 A1



GM, KI, LS, MW, MZ, NA, SD, SI, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *with amended claims*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*